




Gas & Flame Detection



3M™ Detcon™ Model 700 Industrial Gas Detection Sensor



3M™ Detcon™ Model 700


Description

Model 700 industrial gas detection sensors are a new generation of intelligent sensor modules that incorporate and integrate several leading edge improvements. The sensors are specifically designed for harsh and extreme locations. This new and superior level of environmental durability in sensor design includes an electropolished 316 stainless steel housing, multi-layered transient spike protection circuitry and 100% encapsulated electronics. The sensor electronics are completely protected and immune to water ingress and corrosion. The gas detector sensor elements are all plug-in components and can easily be replaced in the field. Operator interface is non-intrusive via a small handheld magnet. Configuration and routine calibration is intuitive and menu driven with fully scripted instructions. Sensor status is displayed on a built-in alphanumeric LED display. Model 700 intelligent sensor modules feature dual redundant outputs, a linear 4 - 20 milliamp analog signal and a Modbus RS-485 serial output.

It is becoming increasingly important that safety systems meet the Safety Integrity Level (SIL) requirements of IEC 61511. The SIL rating can only be determined by considering the complete safety system. The Model 700 sensor modules are designed with this in mind and feature a new and unmatched level of pre-emptive fault diagnostics. Application variables like input voltage range, operating temperature range, maintenance schedule, detector reliability and output integrity are all monitored and reported via the 4 - 20 mA and RS - 485 serial output. As a component of a SIL rated system, the Safe Failure Fraction (SFF) of Model 700 sensors are designed to meet the requirements for any SIL 2 rated system.

Model Series 700 sensors utilize six distinctive gas detection technologies to satisfy a wide range of industrial applications that require monitoring of oxygen, toxic and flammable gases.

Sensors for Hydrogen Sulfide



CHEMFET MOS Solid State Technology

Harsh and Extreme Locations
Wide Temperature & Humidity Range
10-year Sensor Warranty



Electrochemical Technology

Quick Response Time
Long Term Calibration Stability
Low Power Consumption

Sensors for Combustible Gas



Catalytic Technology

Non-selective Combustible Gas Detector
3 to 5 Year Life Expectancy
Rugged Construction



Infrared Technology

Combustible Hydrocarbon Gas Detector
5-Year Warranty
Miniature Plug-in Optical Detector

Sensors for Toxic Gases



Electrochemical Technology

Quick Response Time
Long Term Calibration Stability
Low Power Consumption



Photo Ionization

Universal Non-Selective VOC Sensor
Miniature Plug-in Detector

Oxygen Sensors



Electrochemical Technology

Quick Response Time
Embedded Temperature Compensation
2-year Sensor Warranty

CO2 Sensors




Infrared Technology

CO2 Gas Detector
5-Year Warranty
Miniature Plug-in Optical Detector

3M™ Detcon™ Model 700

Anatomy of a Model 700



3M™ Detcon™ Model 700

Technology Features

Environmentally Bulletproof


- Electropolished 316SS Construction
- 100% Encapsulated Circuitry
- Bullet-Proof I/O Protection
 - Over-voltage
 - Miswiring
 - EMI/RFI Immunity
- Water-Resistant, Corrosion-Resistant, Vibration-Resistant

Gold Plated Mating Pins



Modular and Serviceable

- Modular Design
- Plug and Play Components
- Minimal Spare Parts
 - Universal Design Concept
- Quick Thread Release
 - For Sensor Replacement
- Integral Calibration Port




Failsafe User-Friendly Interface

- LED Display
 - With Antiglare Cover
- Full Text Display Method
- Non-intrusive Interface


Scrolling Full Message/Text Display



Pre-emptive Fault Diagnostics






Auto Zero/Auto Span Sequence



3M™ Detcon™ Model 700

Technology Features

Model 700 gas detectors provide the end-user with a wide variety of output & integration options. The standard intelligent sensor module features an industry standard 4 - 20 mA output and a RS - 485 MODBUS RTU interface. These outputs can be used simultaneously. Additional integration options include a Remote sensor, and WiredHART communications. Shown below are some typical system integration approaches:



Wide Range DCS/DAS and Integration Options

Remote Control
Alarm Relay
Module

Hart RAM
Module

Hart Bridge
Module



3M™ Detcon™ Model 700

Specifications

Common Specifications

Input Voltage

11.5 - 2B VDC standard

Power Consumption

<2 watts typical

Outputs

Linear 4 - 20 mA DC

RS - 485 Modbus™ -RTU

Electrical Classification

Explosion Proof

FP - 700, TP - 700, IR - 700 - LEL, IR - 700 - CO2

Class I, Division 1, Groups B, C, D

II 2G Ex d IIB + H2

DM - 700 Toxics, DM - 700 - O2, PI - 700:

Class I, Division 1, Groups B, C, D

II 2G Ex d ib IIB+H2

Safety Approvals

cCSAus

ATEX

INMETRO

CNEX

PESO

ABS

Dimensions

7" High x 2 1/8" Diameter (sensor only)

Weight

2 Lbs

Functional Safety Rating

IEC 61508 SIL2 Certified (IR, TP, FP, DM)

Exida assessed SIL2 (FMEDA)

Performance Approvals

IR - 700, FP - 700 to ISA 12.13.01:2013, CSA #152

TP - 700, DM - 700 to ISA 92.00.01:1998

Technology Specifications

Accuracy/Repeatability

FP - 700: ±3% 0-50% LEL; ±5% 50-100%

TP - 700: ±10% of reading or ±2 ppm (greater of)

DM - 700 - O2: ±2% full scale

IR - 700 - CH: ±3% 0-50% LEL; ±5% 50-100% LEL

IR - 700 - CO2: ±5% full scale

PI - 700: ±10% of reading: ±2.5% of range (greater of)

DM - 700 (toxics): Contact factory for specific gases

Operating Humidity Range (Continuous)

FP - 700: 0-99% RH non-condensing

TP - 700: 15-100% RH non-condensing

DM - 700 - O2: 0-99% RH non-condensing

IR - 700 - CH: 0-99% RH non-condensing

IR - 700 - CO2: 0-99% RH non-condensing

PI - 700: 0-100% non-condensing

DM - 700 (toxics): typically 10-90% RH contact factory for specific gases

Warranty

TGFD warrants each new Model 700 Intelligent Transmitter Module to be free from defects in material and workmanship under intended normal use for a period of two years from the date of shipment to the original purchaser. TGFD warrants each new plug-in replaceable sensor to be free from defects in material and workmanship under intended normal use for the period described in the table on the left. All warranties are FOB the TGFD factory located in the Woodlands, Texas, USA.

**Standard Range - contact factory for other ranges. **Replaceable plug-in sensor. Contact the factory for other gases not on this list. Cross sensitivity data available on request.*

3M™ Detcon™ Model 700

Ordering Information

Combustible Gas Sensor (matched pair catalytic bead)

Model #	Gas/Symbol	Range ^o	Temperature	Warranty**
FP-700	Combustible Gas	0-100% LEL	-40°C to + 70°C	2 Years

Hydrogen Sulfide Gas Sensor (solid state metal oxide semiconductor)

Model #	Gas/Symbol	Range ^o	Temperature	Warranty**
TP-700	Hydrogen Sulfide/H2S	0-100 ppm	-40°C to + 70°C	10 Year conditional

Oxygen Gas Sensor (galvanic metal air battery)

Model #	Gas/Symbol	Range ^o	Temperature	Warranty**
DM-700-O2	Oxygen/O2	0-25%	-20°C to + 50°C	2 Years

Combustible Hydrocarbon & Carbon Dioxide Gas Sensors (non-dispersive infrared optical - PID)

Model #	Gas/Symbol	Range ^o	Temperature	Warranty**
IR-700-CH	Combustible Hydrocarbons	0-100% LEL	-40°C to + 70°C	5 Years Pro-Rated
IR-700-CO2	Carbon Dioxide/ CO2	0-3%	-40°C to + 70°C	5 Years Pro-Rated

VOLATILE ORGANIC COMPOUND (VOC) GAS SENSORS (photo ionization detector - PID)

Model #	Gas/Symbol	Range ^o	Temperature	Warranty**
PI-700-VOC	Volatile Organic Compounds	0-10 ppm	-20°C to + 50°C	6 Months
PI-701-VOC	Volatile Organic Compounds	0-1,000 ppm	-20°C to + 50°C	6 Months

Toxic Gas Sensors (electrochemical fuel cell)

Model #	Gas/Symbol	Range ^o	Temperature	Warranty**
DM-700-C2H2	Acetylene/C2H2	0-100 ppm	-20°C to + 50°C	2 Years
DM-700-NH3	Ammonia/NH3	0-100 ppm	-20°C to + 40°C	2 Years
DM-700-AsH3	Arsina/AsH3	0-1 ppm	-20°C to + 40°C	1 1/2 Years
DM-700-Br2	Bromine/Br2	0-5 ppm	-20°C to + 50°C	2 Years
DM-700-C4H6	Butadiene/C4H6	0-100 ppm	-20°C to + 50°C	2 Years
DM-700-CO	Carbon Monoxide/CO	0-100 ppm	-40°C to + 50°C	3 Years
DM-700-Cl2	Chlorine/Cl2	0-10 ppm	-20°C to + 50°C	2 Years
DM-701-CLO2	Chlorine Dioxide/ClO2	0-1 ppm	-20°C to + 50°C	2 Years
DM-700-B2H6	Diborane/B2H6	0-5 ppm	-20°C to + 40°C	1 1/2 Years
DM-700-C2H5OH	Ethanol/C2H5OH	0-100 ppm	-20°C to + 50°C	2 Years
DM-700-C2H5SH	Ethyl Mercaptan/C2H5SH	0-100 ppm	-40°C to + 50°C	2 Years
DM-700-C2H4	Ethylene/C2H4	0-100 ppm	-20°C to + 50°C	2 Years
DM-700-C2H4O	Ethylene Oxide/C2H4O	0-100 ppm	-20°C to + 50°C	2 Years
DM-700-F2	Fluorine/F2	0-1 ppm	-10°C to + 40°C	1 1/2 Years
DM-700-CH2O	Formaldehyde/CH2O	0-100 ppm	-20°C to + 50°C	2 Years
DM-700-GeH4	Germane/GeH4	0-2 ppm	-20°C to + 40°C	1 1/2 Years

3M™ Detcon™ Model 700

Ordering Information

Toxic Gas Sensors (electrochemical fuel cell)					
Model #	Gas/Symbol	Range ^o	Temperature	Warranty**	
DM-700-N2H4	Hydrazine/N2H4	0-1 ppm	-10°C to + 40°C	1 Year	
DM-700-H2	Hydrogen/H2	0-100 ppm	-20°C to + 50°C	2 Years	
DM-701-H2	Hydrogen/H2	LEL	-40°C to + 40°C	2 Years	
DM-702-H2	Hydrogen/H2	0-1%	-40°C to + 40°C	2 Years	
DM-700-HBr	Hydrogen Bromide/HBr	0-30 ppm	-20°C to + 40°C	11/2 Years	
DM-700-HCL	Hydrogen Chloride/HCl	0-30 ppm	-20°C to + 40°C	11/2 Years	
DM-700-HCN	Hydrogen Cyanide/HCN	0-30 ppm	-40°C to + 40°C	2 Years	
DM-700-HF	Hydrogen Fluoride/HF	0-10 ppm	-20°C to + 35°C	1 Year	
DM-700-H2S	Hydrogen Sulfide/H2S	0-100 ppm	-40°C to + 50°C	2 Years	
DM-700-CH3OH	Methanol/CH3OH	0-100 ppm	-20°C to + 50°C	2 Years	
DM-700-CH3SH	Methyl Mercaptan/CH3SH	0-100 ppm	-40°C to + 50°C	2 Years	
DM-700-NO	Nitric Oxide/NO	0-100 ppm	-20°C to + 50°C	3 Years	
DM-700-NO2	Nitrogen Dioxide/NO2	0-10 ppm	-20°C to + 50°C	2 Years	
DM-700-O3	Ozone/O3	0-1 ppm	-10°C to + 40°C	2 Years	
DM-700-PH3	Phosphine/PH3	0-5 ppm	-20°C to + 40°C	11/2 Years	
DM-700-SiH4	Silane/SiH4	0-50 ppm	-20°C to + 40°C	11/2 Years	
DM-700-SO2	Sulfur Dioxide/SO2	0-20 ppm	-20°C to + 50°C	2 Years	

Accessories

Description

Remote Control/Alarm Relay Module in NEMA 7 Junction Box (Aluminum or Stainless Steel)

Hart RAM in NEMA 7 Junction Box (Aluminum or Stainless Steel)

Hart Bridge Module in NEMA 7 Junction Box (Aluminum or Stainless Steel)

Foundation Fieldbus Module in NEMA 7 Junction Box (Aluminum or Stainless Steel)

Wireless Interface Module in NEMA 7 Junction Box (Aluminum or Stainless Steel)

Americas Texas (USA)

4055 Technology Forest
Blvd. The Woodlands,
TX 77381
Tel.: +1713 559 9200
Fax: +1713 893 6729

EMEA

ZI Est, Rue Orfila,
CS 20417
62027 ARRAS CEDEX, France
Tel.: +33-3-21-60-80-80
Fax: +33-3-21-60-80-00

Asia Pacific

290 Guiqiao Road
Pudong, Shanghai 201206
People's Republic of China
Tel.: +86-21-3127-6373
Fax: +86-21-3127-6365